

## FLAG Multi-Purpose Metallic Primer



### PRODUCT DATA

---

#### **Description:**

Universal primer suitable for above and below the waterline on all substrates with good waterproofing and corrosion resisting performance. Also suitable as a primer or barrier coat under FLAG and other traditional antifoulings. Contains leafing pigment (excellent sealing/binding properties). Easy to apply and relatively quick drying.

#### **Area of use:**

Boat hulls, topsides and superstructure.

#### **Substrates:**

GRP, wood, steel and ferro cement.

#### **Packing:**

1 litre and 2.5 litre

#### **Physical Constants:**

Colour:	Grey
Finish:	Matt
Volume solids:	60%
Theoretical spreading rate:	12sq.metres per litre
Flash point:	42°C
Specific gravity:	1.17
Dry to touch:	2 hours
Overcoating time:	6 hours

*\*The theoretical spreading rate has been calculated for the stated volume solids and dry film thickness. A practical spreading rate will depend on the actual dry film thickness, the nature of the substrate, and the relevant consumption factor. The physical constants are subject to normal manufacturing tolerances.*

#### **Application Details:**

Application method:	Brush Conventional spray Airless spray Roller
Thinner:	FLAG Antifouling Thinners
Cleaning of tools:	FLAG Antifouling Thinners

#### **Surface condition:**

The surface should be stable, firm, dry and free of dust, sand, loose old paint, dirt, grease, oil and salt.

*Please refer to the Material Safety Data Sheet for further information.  
For additional guidance please contact your local Technical Sales Representative.*