

WP 1307

Teak Treat (Boroquat)

A wood treatment chemical designed to eradicate and prevent mould & algae growth on teak boat decks and any other teak wood exposed to the elements.



BENEFITS

- Removes black mould spores
- Prevents regrowth of mould spores
- No hard work or scrubbing

DESCRIPTION

Teak Treat is a dual purpose product which works by dislodging the black biological residues which can blight a decks appearance.

Its primary use is for treating tired decks which are not soiled with oil or diesel but are in need of a refresh. Over several weeks it will restore the wood back to a clean appearance.

Secondly it can be used as an overwintering solution to preserve the appearance of the wood and prevent greening.

INSTRUCTIONS FOR USE

Teak Treat must be applied to a dry deck. It is normally diluted with between 1 and 3 parts water to 1 part Teak Treat.

Apply liberally to the deck so that the surface is saturated. For best results, a second coat must be applied within a week, also on a dry day. Simply leave the deck and over the course of the next few weeks you will see an improvement to any tired decks and protection from black and green marks. By using this method, some customers have reported their decks to be maintained for up to 2 years.

Please note, there will be NO immediate visible improvement but, over the following weeks, you will see a general lightening of the deck and a significantly improved appearance. Mould algae and algae spots should disappear as Teak Treat detaches the black residues from the decking and allows the elements to wash them away.

PHYSICAL PROPERTIES

Physical state: Liquid
Appearance: Clear, colourless liquid.
Colour: Colourless.
Odour: characteristic.
Flammability (solid, gas): Non-flammable.
Density: 1.054 g/cm³
Solubility: soluble in water.

HEALTH & SAFETY

Danger
H315 - Causes skin irritation
H319 - Causes serious eye irritation
H360 - May damage fertility or the unborn child
H412 - Harmful to aquatic life with long lasting effects
P201 - Obtain special instructions before use
P202 - Do not handle until all safety precautions have been read and understood
P264 - Wash hands thoroughly after handling
P273 - Avoid release to the environment
P280 - Wear eye protection, protective gloves
P302+P352 - IF ON SKIN: Wash with plenty of water
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P308+P313 - IF exposed or concerned: Get medical advice/attention
P332+P313 - If skin irritation occurs: Get medical advice/attention
P337+P313 - If eye irritation persists: Get medical advice/attention
P362+P364 - Take off contaminated clothing and wash it before reuse
P405 - Store locked up
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation
Hazardous ingredients: disodium octaborate

Manufactured by:

**Wessex Chemical Factors
9 Crane Way
Woolsbridge Industrial Park
Three Legged Cross
Wimborne
Dorset
BH21 6FA
United Kingdom**

Tel: 01202 823699

Fax: 01202 813863

Email: info@wessexchemicalfactors.co.uk

Website: www.wessexboatstore.co.uk

